


Bolla Remote

Compact 6, 12 or 24V Remote

Job/Location: _____

Contractor: _____ Prepared By: _____

Model Number: _____ Date: _____



COMPACT DESIGN

The **BOLLA** has been designed to blend into the interior design. The clear polycarbonate lens and white powder coated back plate is neutral for any decor.

EXTERNAL SPECIFICATIONS

The **BOLLA** remote is designed to withstand the elements and abuse in applications such as schools, corridors, institutions and apartment complexes. Universal knockout mounting pattern and key hole slots are cast into the mounting backplate.

MECHANICAL SPECIFICATIONS

The **BOLLA** remote is constructed of white powder coated die-cast aluminum mounting plate with an impact resistant polycarbonate protective lens. The **BOLLA** mounting plate is standard in an attractive powder coated white finish. Other colors are available, including custom color matching.

INSTALLATION


The **BOLLA** series remote is supplied with a universal mounting plate for surface ceiling or wall mount applications. Suitable for indoor applications. The operating temperature is -40°C to +45°C.

ELECTRICAL SPECIFICATIONS

The **BOLLA** series is available with high output LED, MR16 or GU10 lamps.

CSA 22.2 No. 141 performance certified.

DIMENSIONS (MM, IN.)



Series	A	B	C
BOL-R	159mm	210mm	95mm
	6 1/4"	8 1/4"	3 3/4"

LAMP SELECTION

	6V	12V	24V	120V
MR16	6, 10W	10, 12, 20, 35, 50W	10, 12, 25, 50W	N/A
LED-MR16	5, 7W	2, 5, 7W	5, 7W	N/A
GU10	N/A	N/A	N/A	20W

ORDERING INFORMATION

Series	Lamp No.	Voltage/Wattage	Options
BOL-R	1 (single)	See Lamp Selection	CC (Custom colour mounting plate)
	2 (double)		WG (Wireguard)
			TP (Tamper proof screws)

EXAMPLE: BOL-R-2-12V5W-LED

DESCRIPTION: Bolla NEMA 4X Remote, 2 lamp, 12V 5W LED



REMOTES